

according to Regulation (EC) No 1907/2006

Indunorm Anti-Rust 400 ml

Revision date: 10.01.2018 Product code: 93885 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Indunorm Anti-Rust 400 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Polishes and wax blends

1.3. Details of the supplier of the safety data sheet

Company name: Indunorm Hydraulik GmbH

Street: Oderstraße 3

Place: D-47506 Neukirchen-Vluyn

Telephone: +49 28 45 29 50 0 Telefax: +49 28 45 29 50 480

e-mail: info@indunorm.de Internet: www.indunorm.de

1.4. Emergency telephone +49 761 19 240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



according to Regulation (EC) No 1907/2006

	Indunorm Anti-Rust 400 ml	
Revision date: 10.01.2018	Product code: 93885	Page 2 of 8

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Lubricants, greases, release products

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification according to Regulati	on (EC) No. 1272/2008 [CLP]		
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
	919-857-5			
	Flam. Liq. 3, STOT SE 3, Asp. Tox.	1; H226 H336 H304		
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
	927-510-4			
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411	225 H315 H336 H304		
	Hydrocarbons, C9-C10, n-alkanes,		10 - 25 %	
	927-241-2		01-2119471843-32	
Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412				
3010-23-9	4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine			
	221-133-2			
	Skin Corr. 1B, Aquatic Acute 1, Aqu			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).





according to Regulation (EC) No 1907/2006

Indunorm Anti-Rust 400 ml

Revision date: 10.01.2018 Product code: 93885 Page 3 of 8

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After indestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water. Carbon dioxide (CO2). Extinguishing powder. alcohol resistant foam

Unsuitable extinguishing media

Strong water jet

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothes. Wear personal protection equipment. Keep away from sources of ignition - No smoking. Ventilate affected area. Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

The product needs to apply neutralizing agents before draining to wastewater treatment plants. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Advice on protection against fire and explosion

Use water spray jet to protect personnel and to cool endangered containers. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Protect against direct sunlight.

Advice on storage compatibility

Do not store together with:

Strong acid. Oxidizing agents. Alkali (Iye)

Further information on storage conditions

Notice the directions for use on the label.



according to Regulation (EC) No 1907/2006

Indunorm Anti-Rust 400 ml

Revision date: 10.01.2018 Product code: 93885 Page 4 of 8

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
Consumer DNEL, long-term oral systemic 300 mg/kg bw/				300 mg/kg bw/day	
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day	
Consumer DNEL, long-term		dermal	systemic	300 mg/kg bw/day	
Worker DNEL, long-term		inhalation	systemic	1500 mg/m³	
Consumer DNEL, long-term		inhalation	systemic	900 mg/m³	

8.2. Exposure controls

Appropriate engineering controls

No data available

Protective and hygiene measures

Remove contaminated, saturated clothing immediately.

After work, wash hands and face.

When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NR (natural rubber, natural latex) > 0.4 mm, Breakthrough time (maximum wearing time) > 480 min DIN EN 374

Skin protection

Wear suitable protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Use suitable breathing apparatus. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: whitish
Odour: characteristic

Changes in the physical state



according to Regulation (EC) No 1907/2006

Indunorm Anti-Rust 400 ml			
Revision date: 10.01.2018	Product code: 93885	Page 5 of 8	
Melting point:	No data available		

Flash point: -104 °C

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 10,8 vol. %

Ignition temperature: 236 °C

Density (at 20 °C): 0,825 g/cm³

Water solubility: The substance is not soluble in water.

Solvent content: 44%

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours. Exothermic reaction with: Alkali (lye); Strong acid; Oxidising agent, strong

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5. Incompatible materials

Oxidising agent, strong. Strong acid. Alkali (lye)

10.6. Hazardous decomposition products

Hazardous decomposition products: Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

No data available

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat		OECD 401 eq.

Irritation and corrosivity

Irritating to skin. Risk of serious damage to eyes.

Sensitising effects

No data available

Carcinogenic/mutagenic/toxic effects for reproduction


No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available





according to Regulation (EC) No 1907/2006

Indunorm Anti-Rust 400 ml

Revision date: 10.01.2018 Product code: 93885 Page 6 of 8

Aspiration hazard

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

Observations relevant to classification

May be harmful if swallowed, in contact with skin or if inhaled.

Other observations

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.



according to Regulation (EC) No 1907/2006

Indunorm Anti-Rust 400 ml

Revision date: 10.01.2018 Product code: 93885 Page 7 of 8

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg



according to Regulation (EC) No 1907/2006

Indunorm Anti-Rust 400 ml

Product code: 93885 Revision date: 10.01.2018 Page 8 of 8

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: ves

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: butane; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; isobutane;

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%

aromatics

2010/75/EU (VOC): 78 % (550 g/l) 2004/42/EC (VOC): 78 % (550 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

> work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Extremely flammable served

SECTION 16: Other information

⊔222

Relevant H and EUH statements (number and full text)

11222	Extremely naminable aerosor.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airway
11044	0

wavs. H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410 H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)